



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 1/17
Replaced revision:8.0 (Dated: 21/09/2021)

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: PFP90
Product name: PROTEX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: SOLVENT BASED FAST DRYING ANTI-STAIN SURFACE TREATMENT FOR MARBLE, GRANITE, AGGLOMERATE BASED ON MARBLE AND NATURAL STONE.

Identified Uses	Industrial	Professional	Consumer
Solvent-based stain protection	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name: FABER CHIMICA S.R.L.
Full address: Via Ceresani 10
District and Country: 60044 Campo D'Olmo - Fabriano (ANCONA) ITALIA
Tel. 0732627178
Fax 073222395

e-mail address of the competent person responsible for the Safety Data Sheet

quality@fabersurfacecare.com

1.4. Emergency telephone number

For urgent inquiries refer to

Belgium
Centre Antipoisons
c/o Hôpital Militaire Reine Astrid, Rue Bruyn 1, 1120 Bruxelles, Belgium
Phone+32022649636
E-mail info@poisoncentre.be
Croatia
Croatian Institute of Public Health, Division for Toxicology
Borongajska 83g, 10000 Zagreb, Croatia
Phone+38514686910
E-mail toksikologija@hzjz.hr
Denmark
Danish Environmental Protection Agency
Haraldsgade 53, 2100 København Ø, Denmark
Phone+45 72 54 40 00
E-mail mst@mst.dk
Estonia
Health Board
Paldiski road 81,10617 Tallinn, Estonia
Phone+372 794 3500
E-mail clp @ terviseamet.ee, info @ terviseamet.ee
Iceland
Poisons Information Center - Icelandic University Hospital
Fossvogur, Reykjavík, Iceland
Phone+354 543 22 22
E-mail eitur@landspitali.is
Ireland
National Poisons Information Centre



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 2/17
Replaced revision:8.0 (Dated: 21/09/2021)

Beaumont Hospital, Beaumont, Dublin 9., Ireland
E-mail [chemicalsinfo @ beaumont.ie](mailto:chemicalsinfo@beaumont.ie)

Latvia
State Ltd "Latvian Environment, Geology and Meteorology Centre"
Maskavas Street 165, Riga, LV-1019, Latvia
Phone +371 67032600
E-mail lvgmc@lvgmc.lv

Lithuania
Environmental Protection Agency
Juozapavicius st. 9, LT-09311 Vilnius, Lithuania
Phone +370 70662008
E-mail aaa@aaa.am.lt

Malta
Malta Competition and Consumer Affairs Authority (MCCAA)
Mizzi House, National Road, Blata I-Bajda FMR9010, Malta
Phone +356 2395 2000
E-mail info@mccaa.org.mt

Norway
Norwegian Environment Agency
Postboks 5672 Torgarden, 7485 Trondheim, Norway
Phone+4573580500
E-mail produktregisteret@miljodir.no

Portugal
Centro de informação antivenenos
Rua Almirante Barroso, 36 1000-013 Lisboa, Portugal
Phone +351213303271
E-mail ciav.tox@inem.pt

Sweden
Swedish Poisons Information Centre
Giftinformationscentralen 171 76 Stockholm, Sweden
Phone +46104566750
E-mail giftinformation@gic.se

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3

H226

Flammable liquid and vapour.

Specific target organ toxicity - single exposure, category 3

H336

May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Warning



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 3/17
Replaced revision:8.0 (Dated: 21/09/2021)

Hazard statements:

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P312 Call a POISON CENTRE / doctor if you feel unwell.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P370+P378 In case of fire: use carbon dioxide, foam, chemical powder to extinguish.

Contains: N-BUTYL ACETATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
N-BUTYL ACETATE		
CAS 123-86-4	$94 \leq x < 98$	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC 204-658-1		
INDEX 607-025-00-1		
Hydrocarbons C11-14 n-alkanes, isoalkanes, cyclics <2% aromatics		
CAS 64742-47-8	$2,5 \leq x < 3$	Asp. Tox. 1 H304
EC 926-141-6		
INDEX -		
REACH Reg. 01-2119456620-43		
DIPROPYLENE GLYCOL MONOMETHYL ETHER		
CAS 34590-94-8	$1 \leq x < 1,5$	Substance with a community workplace exposure limit.
EC 252-104-2		
INDEX -		

The full wording of hazard (H) phrases is given in section 16 of the sheet.



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 4/17
Replaced revision:8.0 (Dated: 21/09/2021)

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 5/17
Replaced revision:8.0 (Dated: 21/09/2021)

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

**DIPROPYLENE GLYCOL MONOMETHYL ETHER****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	310	50	310	50	
MAK	DEU	310	50	310	50	
VLA	ESP	308	50			SKIN
VLEP	FRA	308	50			SKIN
VLEP	ITA	308	50			SKIN
TGG	NLD	300				
WEL	GBR	308	50			SKIN
OEL	EU	308	50			SKIN

N-BUTYL ACETATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	300	62	600 (C)	124 (C)	
VLA	ESP	241	50	724	150	
VLEP	FRA	710	150	940	200	
VLEP	ITA	241	50	723	150	
TGG	NLD	150				
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

Hydrocarbons C11-14 n-alkanes, isoalkanes, cyclics <2% aromatics**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	310	50	310	50	
VLA	ESP	308	50			SKIN
VLEP	FRA	308	50			SKIN
VLEP	ITA	308	50			SKIN
OEL	EU	308	50			SKIN
TLV-ACGIH		606	100	909	150	SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 7/17
Replaced revision:8.0 (Dated: 21/09/2021)

through effective local aspiration.
When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	typical of solvent	
Melting point / freezing point	< 0 °C	
Initial boiling point	190 °C	
Flammability	flammable liquid	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Flash point	> 27 °C	
Auto-ignition temperature	Not available	
pH	Not available	
Kinematic viscosity	Not available	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	Not available	



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 8/17
Replaced revision:8.0 (Dated: 21/09/2021)

Density and/or relative density	0,89 kg/l
Relative vapour density	Not available
Particle characteristics	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Forms peroxides with: air.

N-BUTYL ACETATE

Decomposes on contact with: water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

May react violently with: strong oxidising agents.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Avoid exposure to: sources of heat.Possibility of explosion.



N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

10.5. Incompatible materials

N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 10/17
Replaced revision:8.0 (Dated: 21/09/2021)

ATE (Inhalation) of the mixture: Not classified (no significant component)
ATE (Oral) of the mixture: Not classified (no significant component)
ATE (Dermal) of the mixture: Not classified (no significant component)

N-BUTYL ACETATE

LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 6400 mg/kg Rat
LC50 (Inhalation vapours): 21,1 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 11/17
Replaced revision:8.0 (Dated: 21/09/2021)

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class



Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

12.1. Toxicity

Information not available

12.2. Persistence and degradability

DIPROPYLENE GLYCOL MONOMETHYL
ETHER

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

12.3. Bioaccumulative potential

DIPROPYLENE GLYCOL MONOMETHYL
ETHER

Partition coefficient: n-octanol/water 0,0043

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3

BCF 15,3



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 13/17
Replaced revision:8.0 (Dated: 21/09/2021)

12.4. Mobility in soil

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, 1123
IATA:

14.2. UN proper shipping name

ADR / RID: BUTYL ACETATES SOLUTION
IMDG: BUTYL ACETATES SOLUTION
IATA: BUTYL ACETATES SOLUTION

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3





FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 14/17
Replaced revision:8.0 (Dated: 21/09/2021)

IATA: Class: 3 Label: 3



ADR / RID, IMDG, III
IATA:

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	Special provision: - EMS: F-E, S-D	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special provision:	A3	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 15/17
Replaced revision:8.0 (Dated: 21/09/2021)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Asp. Tox. 1	Aspiration hazard, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 16/17
Replaced revision:8.0 (Dated: 21/09/2021)

- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:



FABER CHIMICA S.R.L.

PROTEX

Revision n. 8.1
Dated 04/03/2022
Printed on 04/03/2022
Page n. 17/17
Replaced revision:8.0 (Dated: 21/09/2021)

The following sections were modified:
01 / 02 / 03 / 11 / 15.