FLAG STONE FIX
STONE CARE EXPERTS

ZYAX GROUP

Technical Data Sheet (TDS)

FS PEELABLE COATING (SOLVENT BASED)

DESCRIPTION

Strippable Coating or Protective Peelable Coating is a solvent-based peelable coating for temporary protection applications. It is suitable for many substrates including glass, metal, and plastics. It offers temporary protection against dust, stains, grease, and even weld slag. It can easily be peeled off when the protection is no longer required. There is no damage to the surface and there is no residue left on the substrate.

PHYSICAL PROPERTY

TYPE	POLYMER
Viscosity	50-70 SEC sec
Solid	30-40%
Drying time	15 min touch dry,35 min complete dry
color	Green, Orange, Blue
density	1.02-1.1
VOC	60-70%
Flash point	30°c

APPLICATION

Do not thin or reduce. The product is made ready to spray. Apply several coats for adequate coverage.

COVERAGE

First coat on perfectly cleaned glass 120 sq. ft. per liter For the second coat 160 sq. ft. per liter. Two coats are mandatory for better peel-ability. Manufacturer do not give warranty in case single coat is applied.

FEATURES

- This product is acid and alkali-proof.
- Complete hand peelable.
- High film strength.
- Room temperature drying.
- Suitable for use dip, spray or brush.

SELF LIFE OF PACKED MATERIAL

9 months from the manufacturing date.

SHELF LIFE OF APPLIED MATERIAL

- **External or outdoor applications:** 8–9 months
- **Internal or indoor applications:** 15 months

STORAGE

Store in a cool, dry place. Close all containers after use. Do not store near heat or sparks. Spills should be cleaned up with non-sparking tools.

CLEAN UP

Use thinner to clean equipment. Dispose of dirty solvent and cleaning rags in a safe and compliant manner.

NOTE

All information provided is typical (as formulated) and will not represent

FLAGSTONE FIX
ZYAX CHEM PVT. LTD.
Third Floor, Kamer Building, 38, Cawasji Patel Street, Fort, Mumbai, Maharashtra, 400001, India.
☎ +91-8779-240-420 | ✉ info@zyax.in | 🌐 www.flagstonefix.com