Protective

DEEP ENHANCER BLACK

Black coloured enhancer stain-proof impregnator for low absorption materials

DEEP ENHANCER BLACK is a solvent-based impregnator with black pigmentation, specially developed for the most compact and less absorbing surfaces. The product, formulated with high quality pigments, was developed to provide a full-black colour, deep, uniform and long-lasting, without making a film on the surface, despite its application on low absorbing materials.

In fact, **DEEP ENHANCER BLACK** enhances the colour and beauty of material without incurring a greasy patina. The product covers possible defects or crackling that reduce the evenness of black materials. Besides offering excellent water- and oil-repellent features on the most compact surfaces, allows vapour transpiration.

CHARACTERISTICS AND BENEFITS

- ✓ High stain proof capacity
- ✓ Provides hydro-repellency to the surface
- ✓ Provides oleo-repellency to the surface
- ✓ Strong colour enhancer
- ✓ No patina
- ✓ Resistant against UV rays
- ✓ Non-yellowing

USES

For interiors and exteriors on black materials; Marbles, polished and brushed travertines and granites, quartz agglomerates and porcelain stoneware.

COVERAGE

20/30 m^2/lt

APPLICATION EQUIPMENT

Brush, Lambswool applicator, Roller, Cloth

APPLICATION STEPS

Test on a small area before proceeding, so to ensure product suitability and final result.

Use the product undiluted.

Apply DEEP ENHANCER BLACK to a clean and dry surface with a brush, a sponge or a sprayer. Wait about 10 to 15 minutes (depending on the absorption capacity of the material) for solvent evaporation, then remove the residue with a scrubbing brush or using a single disc machine with cotton cloth or blotting paper.

Remove any product excess until you will get a dry surface, even to touch.
After carefully removing the residue, wait 4 to 6 hours at least before reopening the area to foot traffic.

If more than one coat is necessary, because of the high absorption capacity of the material, wait until the first coat has dried, 30 minutes at least before applying the second one.

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – **ITALY**
Phone: +39 0732 627178 | **Fax**: +39 0732 22935 | **Email**: info@faberchimica.com

FABERSURFACECARE.COM

Protective

DEEP ENHANCER BLACK *Black coloured enhancer stain-proof impregnator for low absorption materials*

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using with spirit.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATION	
Aspect:	Liquid
Color:	Transparent
Odour	Mineral spirit
Specific Gravity at 20°C	810 ± 10 g/lt.
Flash point (ASTM D 56)	30°C open vase

PRECAUTIONS:

Never apply to wet nor to overheated surfaces

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 1 lt bottles – 12 per carton
- 5 lt containers – 4 per carton

HAZARD IDENTIFICATION



H225	Highly flammable liquid and vapours
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking
P210	Keep far from heat sources / sparkles / free flames / heated surfaces. Do not smoke.
P261	Avoid breathing dust / fume / gas / mist/ vapours /spray.
P331	DO NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove contaminated clothing. Rinse skin/take a shower

Version 2.1 – 11/10/2017

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – **ITALY**
Phone: +39 0732 627178 | **Fax**: +39 0732 22935 | **Email**: info@faberchimica.com

FABERSURFACECARE.COM