Protective

SOL 170

Solvent-based water-repellent in-depth impregnator

SOL 170 is a solvent based concentrated water-repellent impregnator with high penetration for any type of material.

The product has many features and it is recommended both as a pre-treatment, to make washing of absorbing supports easier and as a water-repellent treatment for interior and exterior surfaces, even undergoing dampness from the back side. The protection stays effective even after cleaning with acid products.

Notwistanding a solvent based product, it is low odour and does not change the colour shade of the treated material.

CHARACTERISTICS AND BENEFITS

- ✓ Excellent water-repellent capacity
- ✓ High penetration
- ✓ Not creates film
- ✓ Breathable
- ✓ Non yellowing and UV resistant

USES

Terracotta tiles, brick, marbles, granites, Tuff, porous stones, agglomerates and concrete.

COVERAGE

8/15 m^2/lt

APPLICATION EQUIPMENT

Brush, Lambswool applicator, Roller, Cloth

APPLICATION STEPS

Test on a small area before proceeding, so to ensure product suitability and final result.

The product must be applied undiluted, evenly and generously, following the coverage.

Pre-treatment in the job site

Before setting or grouting of an absorbing material, apply the product to a dust-free, clean and dry material, by immersion, with a sprayer or using a brush.

The product penetrates without leaving any excess nor superficial residues, leaving the colour shade unchanged.

After treatment, wait 24 hours at least before setting or grouting. The product application will allow an easier cleaning of grout residues and end of setting washing.

FABERSURFACECARE.COM

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – **ITALY**
Phone: +39 0732 627178 | **Fax**: +39 0732 22935 | **Email**: info@faberchimica.com

Protective

SOL 170 *Solvent-based water-repellent in-depth impregnator*

Water-repellent application

As a water-repellent treatment before applying any other protective or finishing product, apply to a clean and dry surface, with a sprayer or a brush, always evenly. The product penetrates and dries alone, but avoid any excess and remove possible product accumulations.

Wait 4 to 6 hours before restoring foot traffic on the surface

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using with spirit.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATION	
Aspect:	Liquid
Color:	Colourless
Odour	Mineral solvent
Specific Gravity at 20°C	795 ± 20 g/lt.
Flash point (ASTM D 56)	30°C open vase

PRECAUTIONS:

Never apply to wet nor to overheated surfaces

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 1 lt bottles – 12 per carton
- 5 lt containers – 4 per carton
- 10 lt container – in bulk



HAZARD IDENTIFICATION

R10	Flammable
R65	Harmful: may cause lung damages if swallowed
R66	Repeated exposure to vapors may cause skin dryness or cracking
S2	Keep out of the reach of children
S16	Keep away from sources of ignition and – No smoking
S23	Do not breathe fumes or vapours
S24	Avoid contact with the skin
S25	Avoid contact with eyes

Version 2.0 – 16/01/2017

This **technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.** *The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.*

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – **ITALY**
Phone: +39 0732 627178 | **Fax**: +39 0732 22935 | **Email**: info@faberchimica.com

FABERSURFACECARE.COM