Protective

TX 8

Concentrated water-based stain-proof water repellent treatment for natural stones

TX 8 is a water base impregnator to dilute, for natural stones. Its special formulation is developed to grant an excellent stain proof capacity to polished natural materials and finely honed materials, without changing their color. This treatment is often recommended before setting to avoid adsorption stain on the stone, but can also be applied after setting, before grouting.

The product does not remarkably alter the glue adhesion with the backside of the set materials

CHARACTERISTICS AND BENEFITS

- ✓ Excellent stain-proof features on polished and finely honed materials
- ✓ Provides hydro-oleo repellency to the surface of polished and finely honed materials
- ✓ Does not change the colour of the material
- ✓ Long-lasting solution
- ✓ Does not create film or patina

USES

Interiors and exteriors. Marbles, granites and natural stones. Do NOT apply to dark materials or make a previous test to check the proper method of application and avoid superficial whitish residues.

COVERAGE

21-24 m²/l (for dilution 1:4)

23-26 m²/l (for dilution 1:5)

1 liter of pure product can cover, after dilution, about 130 m²

APPLICATION EQUIPMENT

Brush, Lambswool applicator, Roller, Cloth

APPLICATION STEPS

Test on a small area before proceeding, so to ensure product suitability and final result.

Dilute the product 1:4 (1 part of product in 4 parts of water, 5 total parts) or 1:5 (1 part of product in 5 parts of water, 6 total parts) in tap freshwater, then apply evenly and generously, according to the coverage ratio.
The product can be applied in the factory plant or in the job site, before or after setting.
Apply the product to a dust free, dry or slightly damp material, by immersion, with a sprayer, a brush or with a lamb's skin wool.
After 5 to 10 minutes (just a few seconds in the factory plant) even out the product left on the surface with a lamb's skin wool, a brush or a roller, spreading it until all of the residues are removed.

After treatment, wait 24 hours at least before setting or grouting.

FABERSURFACECARE.COM

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – **ITALY**
Phone: +39 0732 627178 | **Fax**: +39 0732 22935 | **Email**: info@faberchimica.com

Protective

TX 8 *Concentrated water-based stain-proof water repellent treatment for natural stones*

LINEA PROFESSIONALE

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATION	
Aspect:	Liquid
Color:	Transparent
Odour	Light, typical
Specific Gravity at 20°C	1095 ± 10 g/lt
pH	11.0 ± 0.4

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 5 lt containers – 4 per carton

HAZARD IDENTIFICATION



H315	Causes skin irritation
H319	Causes serious eye irritation.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/clothing/eye protection/ face protection.
P302+P352	IF ON SKIN : wash with plenty of water and soap.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: call for a doctor.
P362	Take off contaminated clothing and wash them before reusing.

Version 4.1 – 22/04/2021

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet. *The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.*

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – **ITALY**
Phone: +39 0732 627178 | **Fax**: +39 0732 22935 | **Email**: info@faberchimica.com

FABERSURFACECARE.COM